

THE BANK OF MYSORE, LIMITED, BANGALORE.

Statement of the affairs of the Bank of Mysore, Limited, for the week ending 9th February 1939, published under Article 141 of the Articles of Association.

LIABILITIES		ASSETS	
	Rs.		Rs.
To Capital Receipts ..	20,00,000	By Cash in hand and at Bankers ..	14,29,849
„ Reserve Fund ..	26,50,000	„ Loans and Cash Credit Accounts ..	1,86,48,831
„ Public and other Deposits ..	2,61,61,518	„ Bills discounted and purchased ..	9,48,875
„ Sundries ..	1,76,540	„ Investments ..	90,98,423
		„ Balance at Agencies ..	
		„ Dead Stock ..	7,87,176
		„ Sundries ..	74,904
Total	3,09,88,058		
(Annas and pies omitted.)		Rs.	3,09,88,058

BANGALORE,
Dated 13th February 1939.

F. L. PERADON,
Manager.

GOVERNMENT OF MYSORE, STORES PURCHASE COMMITTEE, BANGALORE.

No. S. P. C. 21187-95, dated 8th February 1939.

To

The Firms dealing in Pneumatic Tyred Water Carts.

Enquiry No. 3294.

PNEUMATIC TYRED WATER CARTS.

DEAR SIR/GENTLEMEN,

Please be good enough to intimate your best prices and the earliest time of delivery for the materials described in the attached schedule, in the form printed below.

It should be distinctly understood that the acceptance by us of your quotation will be subject to the following conditions:—

Withdrawal from the quotation after it is accepted or failure to make the supply within the specified time or according to specifications will entail cancellations of the order and purchases being made at your expense from other sources in addition to the levy of a penalty of 3 per cent of the value of the order as and by way of liquidated damages. In such an event, the Stores Purchase Committee reserve the right to remove your name from the list of approved firms.

The quotations should be superscribed "Quotations for Pneumatic Tyred Water Carts" with the above enquiry Number.

This enquiry will be closed on the 25th February 1939.

Schedule.

Item No.	Description of material offered	Quantity	Price quoted	Time of delivery
			F. O. R.	
1	Mild Steel Welded Water Tank Carts.—Capacity 300 gallons: 3'-1½" diam. × 6'-6" long. The tank should be constructed with ½" thick plates and should be provided with a 16" dia. manhole with hinged cover, ¾" thick M. S. side brackets, flat iron clamps for securing the tank to a square axle, 1. ½" thick baffle plate inside the tank, a 2½" wrought iron pipe drawbar with venteak yoke for two bullocks and 2" wheel valve outlet, with suitable tyres and tubes of size 7.00—19 H. S.	One set.	Mysore.	